

## DAUBERT VCI<sup>®</sup> NOX-RUST<sup>®</sup> LIQUID 5200

PETROLEUM-BASED, SOLVENT-TYPE, COLD APPLIED RUST PREVENTIVE  
(GREASY, SOFT FILM)

**Nox-Rust<sup>®</sup> 5200** is recommended for long-term protection in applications where there is no direct exposure to weather. Indoors, Nox-Rust 5200 will protect interior and exterior surfaces of machinery, instruments, bearings or materials with or without supplemental barrier materials. Outdoors, it will protect for limited periods of time in moderate temperatures. Available in 55-gallon drums and 5-gallon pails.

**Nox-Rust 5200** is completely miscible with lubricating oils, eliminating the need to remove coatings in some applications.

**Nox-Rust 5200** meets the requirements of U.S. Department of Defense military packaging standard Mil-C-16173E, Grade 2, Class 1).

### PHYSICAL CHARACTERISTICS (Typical Values, Not Specifications)

Application	Dipping, spraying or brushing down to +40°F.
Removal	Conventional cleaning procedures or petroleum solvents, alkali or emulsion cleaners.
Film Type	Brown colored, grease-like film
Specific Gravity @ 72°F.	0.85
Pounds/Gallon	7.05
Flash Point	105°F. (min.)
Film Thickness	0.6 mils
Setting Time	30-45 min.

### PROTECTIVE PROPERTIES (Typical Values)

Indoor Storage	5 years (min.)
Outdoor Storage (covered)	1 year (min.)
5% Salt Spray (ATSM-B-117)	7 days
Humidity Cabinet (ASTM-D-1748)	30 days

JK 4/22/03

The data, statements and recommendations in this product information sheet are based on testing, research and other development work, which has been carefully conducted by us, and we believe such data, statements and recommendations will serve as reliable guidelines. Physical properties shown above represent typical values and are not intended for use in writing specifications. However, this product is subject to numerous uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any particular use. Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use.

**WARRANTY** – All products manufactured by us are warranted to be first class material and free from defects in material and workmanship. Liability under this warranty is limited to the net purchase price of any such products proven defective or, at our option, to the repair or replacement of said products upon their return to us transportation prepaid. All claims on defective products must be made in writing within 30 days after the receipt of such products in your plant and prior to further processing or combining with other material and products.

WE MAKE NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY OF ANY OF OUR PRODUCTS FOR ANY PARTICULAR USE, AND WE SHALL NOT BE SUBJECT TO LIABILITY FROM ANY DAMAGES RESULTING FROM THEIR USE IN OPERATIONS NOT UNDER OUR DIRECT CONTROL.

THIS WARRANTY IS EXCLUSIVE OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AND NO REPRESENTATIVE OF OURS OR ANY OTHER PERSON IS AUTHORIZED TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF OUR PRODUCTS.